

Hydraulic Power Supply







Hydraulic Power Supply



Product Overview

LINK's Hydraulic Power Supply product line offers robust, flexible, and dependable solutions for supplying hydraulic power to your test systems. Multiple models are available to meet each customer's unique needs.

Applications

 Used to hydraulically power test systems, specifically dynamic servo-hydraulic and test system applications.













Key Benefits

- Customizable to fit your needs, including specialty fluids, Skydrol, ATF.
- Low noise levels
- Green, earth-friendly design
- The Hydraulic Control Manifold can be incorporated into the Hydraulic Power Supply for increased benefits
 - o Reduced floor space
 - o Increased simplicity
- Temperature, flow, and filter monitoring
- Integrated control for test systems

Specifications

Model Code		HPS-10	HPS-20	HPS-30	HPS-45
Flow Rate (GPM/LPM)	60 HZ	10/38	20/76	30/114	45/170
	50 HZ	8.3/31.6	16.6/63.2	25/95	37.5/142
Foor Print	Inches	42 x 54	42 x 54	40 x 54	40 x 54
	Meters	1 x 1.4	1 x 1.4	1 x 1.4	1 x 1.4
Motor Rating	460VAC/60HZ	20 HP	40 HP	75 HP	100 HP
	380VAC/50HZ	15 KW	30 KW	55 KW	75 KW
Weight (LBS/KG)	Full	2700/1230	2700/1230	3450/1560	3450/1560
	Empty	2250/1022	2250/1022	2500/1140	2500/1140
Resevoir Size	GAL/LITER	75/290	75/290	125/475	125/475
Water Flow	GPM/LPM	5/19	10/38	15/57	22/84

Link Engineering Company

We design and manufacture precision test equipment, and provide comprehensive laboratory and vehicle level testing services. Our specialty is developing innovative custom solutions.

> Visit www.linkeng.com or call 1-734-GET-LINK



PROUDLY SERVING THESE INDUSTRIES















